

OFFICE OF THE PRINCIPAL

CACHAR COLLEGE

REACCREDITED BY NAAC WITH "B" GRADE TRUNK ROAD, SILCHAR-788001 (ASSAM) ESTD: 1960



AFFILIATED TO: ASSAMIUNIVERSITY, SILCHAR

Phone: 03842-246953 (Office)

03842-247077 (Principal)

Fax: 03842-261842

URL:

http://www.cacharcollege.ac.in

E-mail: cacharcollege60@gmail.com

Ref. No. CC/Estd/Adv/Cons/2025/384

Date:-02/12/2025

Sealed Quotation only in Letter Head is hereby invited from the reputed Firms/Contractors having experience in same nature of work for the following work and will be received by the undersigned up to 2.00 PM on 06-12-2025 and will be opened on the same date and place at 3.00 PM by the undersigned or officer authorised by him in presence of intending tenderers or their authorised agents, if any one like to remain present.

In case any unavoidable circumstances or any Govt. holiday declared on that day, then the tender will be received and opened on the next working day at the same place and hour.

| Name of the work | Stipulated period of completion |
|---|---------------------------------|
| Repair & renovation work of room no. 219 to setting up Language Laboratory at Cachar College Silchar under PM USHA-Fund | 15 Days |

The rate to be quoted in item basis (Square Meter/ Cubic Meter whichever is applicable) & inclusive of all taxes.

- The undersigned reserves the right to accept or reject any or all quotation without assigning any
 reason thereof.
- 2. The undersigned is not bound to accept the lowest quoted rate.
- Payment will be regulated proportionate to physical progress and subject to the availability of fund.
- Detail specification of item of works may be seen in the college during office hours upto 3:00 PM.

Copy to:

- · Office Record
- College Website

Cachar College, Silchar

Principal

Cachar College, Silchar-1

OFFICE OF THE PRINCIPAL



CACHAR COLLEGE

REACCREDITED BY NAAC WITH "B" GRADE TRUNK ROAD, SILCHAR-788001 (ASSAM) ESTD: 1960



HELLATED TO ASSAM UNIVERSITY SUGLAR

Phone: 03842-246953 (Office)

03842-247077 (Principal)

Fax: 03842-261842 URL: E-mail:

http://www.cacharcollege.ac.in cacharcollege60@gmail.com

Items of works

- Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead: Of area 3 sq. metres and below.
- Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in: 6.4.1 Cement mortar 1:4 (1 cement : 4 coarse sand).
- CEMENT PLASTER (IN COARSE SAND)
 - 12 m cement plaster of mix: 1:4 (1 cement: 4 fine sand).
- Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. With float glass panes of 5 mm thickness.
- Providing and fixing 35 mm thick factory made laminated veneer lumber door shutter conforming to IS: 14616 and TADS 15:2001 (Part B), fixing with butt hinges of required size with necessary screws, all complete as per directions of Engineer- in-charge and panelling with panels of: 12 mm thick one side Pre-laminated particle board (decorative lamination on one side and other sides balancing lamination) grade -1, medium density flat pressed, three layer particle board FPT - I or graded wood particle board FPT-1 conforming to IS: 3087 bonded with BWP type synthetic resin adhesive as per IS: 848 and pre-laminated conforming to IS: 12823, Grade -1,
- Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. Fixed to openings /wooden frames with rawl plugs screws etc.
- Providing and laying vitrified floor tiles of size 24" x 24" (thickness to be specified by the manufacturer) with water absorption less than 0.08% and conforming to IS: 15622, of approved make, in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand), jointing with grey cement slurry @ 3.3 kg/ sqm including grouting the joints with white cement and matching pigments etc., complete. Size of Tile 600x600 mm.
- Providing and laying Vitrified tiles of size 24" x 24" (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joint with white cement & matching pigments etc. complete. Size of Tile 600x600 mm.

Cachar College, Silchar

Principal Cachar College, Silchar